



# 05000ST Motor Oil 5W-30 Premium Synthetic ST

Dokumentversion: 13.04.2024



## Beschreibung

This Premium Synthetic 'Mid SAPS ' engine oil is designed for gasoline and diesel engines equipped with an exhaust after-treatment system. This special formulation complies to the Stellantis FWP9.55535/03 specification which is mandatory for DV5R engines until OPR 16885. These D5VR engines are used in Citroën, DS, Peugeot, Fiat, Toyota, Opel and Vauxhall. The optimized cleanliness, reduces wear increases the lifetime of the mechanical components and the engine. This engine oil is also suitable for engines requiring PSA B71 2290 specification with viscosity grade 5W-30.

## Anwendungshandbuch

## Spezifikationen

ACEA C3  
API SN Plus

## Empfehlungen

PSA B71 2290  
Stellantis FPW9.55535/03

## Verpackungseinheiten

ART.-NR.	VOLUMEN	ARTIKEL PRO EINHEIT	ARTIKEL PRO PALLETTE
05001ST	1 L	6	450
05005ST	5 L	4	112
05020ST	20 L	1	30
05060ST	60 L	1	6
05205ST	205 L	1	2
P05000ST	1 L	1	-

## Standardanalyse

TEST	WERT		METHODE
Density bei 15°C	0.847	kg/l	ASTM D4052
Kinematic Viscosity bei 40°C	66.3	mm <sup>2</sup> /s	ASTM D445
Kinematic Viscosity bei 100°C	11.3	mm <sup>2</sup> /s	ASTM D445
Viscosity Index	170		ASTM 2270
Flashpoint COC	254	°C	ASTM D92
Pourpoint	-42	°C	ASTM D97

Diese Werte sind typisch für die aktuelle Produktion. Abweichungen dieser Werte können auftreten.